

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
13 October 2005 (13.10.2005)

PCT

(10) International Publication Number
WO 2005/094296 A3

(51) International Patent Classification⁷: **B66C 13/04**

(21) International Application Number:
PCT/US2005/010302

(22) International Filing Date: 28 March 2005 (28.03.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/556,577 26 March 2004 (26.03.2004) US

(71) Applicant (for all designated States except US): **ACTU-
ANT CORPORATION** [US/US]; 720 West James Street,
Columbus, WI 53925 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GONZALEZ,
Jesus** [ES/ES]; Costa Azul St., 17, E-28440 Guadarrama
(ES). **SORDO, Luis** [ES/ES]; Calle San Jose Artesano
N.8, E-28108 Alcobendas (ES).

(74) Agent: **RADLER, Daniel, G.**; Quarles & Brady LLP, 411
East Wisconsin Avenue, Milwaukee, WI 53202 (US).


(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY,
TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU,
ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
— with international search report

[Continued on next page]

(54) Title: HYDRAULIC AUXILIARY HOIST AND CRANE CONTROL FOR HIGH PRECISION LOAD POSITIONING



(57) Abstract: A hoist for positioning a load (40) includes a plurality of lift cylinders (15), a plurality of position sensors, a plurality of electronically controlled valves, a user input device (22), and a hoist controller (20). Each of the hydraulic hoist cylinders is coupled at one end to the hoist and at an opposite end to the load at a lifting point (45). Each of the position sensors is associated with one of the hoist cylinders and operable to provide position data for the associated hoist cylinder. The electronically controlled valves are hydraulically coupled to the hoist cylinders for extending and retracting the associated hoist cylinders. The user input device is operable by a user to specify load data. The hoist controller is operable to receive the load data from the input device and the position data from the position sensors and in response thereto to control the electronically controlled valves so as to position the load according to the load data.

WO 2005/094296 A3



(88) Date of publication of the international search report:

6 April 2006

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.